



## *GE Series II Improved Imitation Mirror (92-671)*

GE Series II Improved Imitation Mirror is an exceptional mirror-like product that utilizes vacuum-metallized pigments to provide a bright silver effect when printed second surface on transparent substrates.

### **Product Description**

Our GE Series II Improved Imitation Mirror is a single-component formulation that has been developed to create superior metallic, mirror-like brilliance. It offers excellent printing and design flexibility to grant versatility when producing high impact visual effects.

### **Suggested Uses**

GE Series II Improved Imitation Mirror gives the brightest results when applied on smooth impervious surfaces.

### **DIRECTIONS FOR USE**

Pretest for adhesion to all substrates prior to production printing, as well as, other properties to determine suitability. Mix well prior to each use.

**Surface** - A clean dry surface is preferred for superior adhesion.

**Mesh** - Monofilament polyester or nylon, 200-305 mesh per inch recommended.

**Stencil** - Lacquer proof, most direct or direct/indirect work well.

**Squeegee** - An 80 durometer (Shore A Hardness) polyurethane is recommended. It should be well sharpened.

**Screen Wash Up** - A special high flash point wash containing no hydrocarbon solvents should be used, such as KOLORCURE'S UVW-80 Screen Wash.

**Screening equipment** - Hand, semi-automatic, or fully automatic presses.

### **ADDITIVES**

To lower the viscosity which will enhance the transfer of the ink through the screen, use GE Series Reducers.